

- Male-to-male is not a standard USB cable configuration. It's used only in rare instances where a peripheral or patch bay employs a female connector instead of a USB-B port.
- This cable will not connect two PCs. File-sharing between computers requires special software-driven cables.

## USB 3.0 SuperSpeed A to A Cable for Tripp Lite USB 3.0 All-in-One Keystone/Panel Mount Couplers (M/M), Black, 6 ft. (1.83 m)

MODEL NUMBER: U325-006



Connects peripherals, patch bays and Tripp Lite USB All-in-One Keystone/Panel Mount Couplers with female USB-A ports to your computer, laptop or other compatible USB device, such as a Chromebook™ or Microsoft® Surface®.

### Features

#### USB Cable Connects USB Type-A Peripherals to Your Computer

This USB-A to USB-A cable is ideal for connecting high-speed USB 3.2 Gen 1 equipment, such as a patch bay or other USB peripherals, to your computer, laptop or other compatible device, such as a Chromebook or Microsoft Surface. Additionally, the U325-006 cable is recommended for use with Tripp Lite's U325-000-KP-BK, U325-000-KPA-BK and U325-001-KPA-BK USB couplers.

#### Supports USB 3.2 Gen 1 Speeds for a Faster, More Efficient Signal

The U325-006 supports USB 3.2 Gen 1 data transfer rates up to 5 Gbps—10 times faster than USB 2.0. Its bi-directional data interface allows data to flow both directions simultaneously, increasing theoretical bandwidth by 10 times for efficient power and little wait-time. The U325-006 is also backward compatible with previous USB generations, so you can continue to use legacy USB 2.0 and USB 1.1 peripherals.

#### Filtering EMI/RFI Line Noise and Eliminating Cable Strain Help Your Equipment Perform Better

Foil and braid shielding blocks disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your electronics and inflict hardware damage or data loss. Integral strain relief gives the U325-006 extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332205100 |

### Highlights

- Supports USB 3.2 Gen 1 speeds up to 5 Gbps to ensure fast data transfers
- Backward compatible with legacy USB 2.0 and USB 1.1 peripherals
- Foil/braid shielding protects against EMI/RFI line noise that can distort or destroy data
- Integral strain relief helps cable move freely without stress or cracking
- Plug-and-play operation with no drivers required for easy, immediate installation

### System Requirements

- Computer with USB-A female port
- Peripheral or patch bay with USB-A female port

### Package Includes

- U325-006 USB 3.2 Gen 1 SuperSpeed A/A Cable (M/M), Black, 6 ft.



|                                      |  |
|--------------------------------------|--|
| Technology                           | USB; USB 3.x   |
| Host Connector                       | USB A (MALE)   |
| USB Cable Type                       | Passive  |
| <b>PHYSICAL</b>                      |  |
| Material of Construction             | PVC  |
| Cable Jacket Color                   | Black  |
| Cable Jacket Rating                  | VW-1   |
| Cable Outer Diameter (OD)            | 5.5mm  |
| Cable Length (ft.)                   | 6  |
| Cable Length (m)                     | 1.83   |
| Cable Length (in.)                   | 72   |
| Cable Length (cm)                    | 182.9  |
| Shipping Dimensions (hwd / in.)      | 0.50 x 7.00 x 9.00   |
| Shipping Dimensions (hwd / cm)       | 1.27 x 17.78 x 22.86   |
| Shipping Weight (lbs.)               | 0.40   |
| Shipping Weight (kg)                 | 0.18   |
| <b>ENVIRONMENTAL</b>                 |  |
| Operating Temperature Range          | 14 to 122 F (-10 to 50 C)  |
| Storage Temperature Range            | 5 to 140 F (-15 to 60 C)   |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing   |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing   |
| <b>CONNECTIONS</b>                   |  |
| Side A - Connector 1                 | USB A (MALE)   |
| Side B - Connector 1                 | USB A (MALE)   |
| Connector Plating                    | Nickel   |
| Contact Plating                      | Gold   |
| <b>FEATURES &amp; SPECIFICATIONS</b> |  |
| USB Specification                    | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps); USB 3.2 Gen 1 (up to 5 Gbps) |
| <b>STANDARDS &amp; COMPLIANCE</b>    |  |
| Product Compliance                   | RoHS; REACH  |
| <b>WARRANTY &amp; SUPPORT</b>        |  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |                           |
|--|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|--|---------------------------|

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>